

FEATURES

- Fixed 50, 60 or 400Hz and variable frequency
- Multi-pulse input transformer for low input current distortion
- Small footprint
- Easy installation

BL PLUS 60KVA, 3-PHASE OUTPUT

60 KVA OF AC POWER IN A CABINET ONLY 27"W X 36"D

Behlman's BL Plus solid state AC power frequency converter offers greater efficiency, reduced downtime, and a significantly smaller footprint and easier installation than the motor generator it is designed to replace. The BL Plus has all the quality features you expect from Behlman; fully adjustable voltage and frequency, low output THD, high efficiency plus excellent line and load regulation. There's also a unique overload protection system that folds-back voltage to maintain rated current without output waveform distortion. The BL Plus optional manual controller has three DMM's for volts, frequency and current and a oscillator that has three fixed frequencies of 50 Hz, 60 Hz and 400 Hz as well as a variable frequency of 45-500 Hz. Optional analog remote control is available with the standard controller or you can opt for the Programmable Controller with RS232 interface standard or optional IEEE-488.

Small size, easy installation, quiet operation and high efficiency make the BL Plus ideal for industrial product testing, precision avionic test, power conversion, ATE, bulk power and motor generator replacement.



BL+60 shown with PAC2000 Controller

INPUT

Multi-pulse input transformer for low input current THD

Voltage/frequency:

C1: 120/208, 57-63 Hz	C6: 230/400, 47-63 Hz
C2: 220/380, 47-53 Hz	C7: 240/415, 47-53 Hz
C3: 277/480, 57-63 Hz	X: Custom input
C4: 200 delta, 57-63 Hz	

OUTPUT

Power:	60 KVA
Voltage:	-XXX: Fixed at any L-N voltage
Accuracy:	0.25% of Full Scale +/- 1 V
	-1: 0-132 VAC, L-N, 3 phase
	-2: 0-264 VAC, L-N, 3 phase
	-3: 0-305 VAC, L-N, 3 phase
Frequency:	-XXX: Fixed at any frequency from 45-500 Hz
Accuracy:	+/- 0.1 Hz
Current:	-1: 152 Amps/phase @ 0-132 V
	-2: 76 Amps/phase @ 0-264 V
	-3: 66 Amps/phase @ 0-305 V
Accuracy:	2% of Full Scale +/- 1 A
Peak current:	Repetitive peak not to exceed 250 amps
Power Factor:	100% of rated output into any power factor load
Distortion:	3.0% THD typical, measured at full current 115 Volts, 60 Hz, into a linear load
Line Regulation:	+/- 0.5% for +/- 10% line change
Load Regulation:	+/- 0.7%, no load to full load
Efficiency:	80% typical
Line drop compensation:	+10% adjustment range to compensate for output line losses

PROTECTIVE CIRCUITS

Input:	Electron ic circuit breaker
Constant Current:	Overload automatically causes voltage fold-back to provide maximum current without distorting output waveform
Short Circuit:	Short-circuit overload electronically latches output open to protect load... power restored by recycling circuit breaker
Thermal:	Internal temperature sensor prevents heat dama ge by turning output off...output will turn on when reaching safe temperature

CONTROLS / INDICATORS

Power On/Off:	Push to start...push to stop
Line drop compensation:	Three recessed potentiometers for 10% adjustment phase A, B, C

AC Power Source/ Frequency Converter

MECHANICAL SPECIFICATIONS

Dimensions: including fork lift base

- 1: 72"H x 36"D x 27"W, plus 6"D junction box
(182.9 cm x 91.4 cm x 68.6 cm)
- 2: 72"H x 36"D x 27"W, plus 6"D junction box
(182.9 cm x 91.4 cm x 68.6 cm)
- 3: 72"H x 36"D x 27"W, plus 6"D junction box
(182.9 cm x 91.4 cm x 68.6 cm)

Weight:

- 1: 2000 lbs. (908 kg)
- 2: 2450 lbs. (1112 kg)
- 3: 2450 lbs. (1112 kg)

Operating Temperature: 32 to 104° F, (0 to 40° C)

Storage Temperature: -4 to 158° F, (-20 to 70° C)

Humidity: 0-95 RH non-condensing

Input Connections: Four pressure terminals:
A, B, C, N...protective ground stud provided

Output Connections: Four pressure terminals:
A, B, C, N

OPTIONS: contact factory for additional options including custom input and output

WF: "Wild Frequency" range of 350 to 880 Hz

M: **MAC2000** manual controller with three fixed frequencies of 50 Hz, 60 Hz
and 400 Hz and variable frequency of 45-500 Hz



P: **PAC2000** programmable controller with 40 characters X 2 line Vacuum Fluorescent display
and front panel pushbutton control or remote control using RS232 interface supplied with controller

P3: Programmable Controller with independent Voltage adjust A, B, C with RS232 Interface



Set: Volts, frequency, current limit, phase angle and output On/Off

Display: Volts A, B, C; current A, B, C; frequency, current limit and fault indication for over voltage (O/V),
over current (O/I), over temperature (O/T), constant current (C/C) and overload latch (O/L),
watts (W), power factor (PF)

Remote sense in place of line drop compensation.

PI: PAC2000 controller with IEEE-488 interface

P3I: Programmable Controller with independent Voltage adjust A, B, C with IEEE-488 Interface

MODEL SELECTION GUIDE

Model BL+60-3-(Input)-(Output)-(Fixed frequency and/or Options)

Examples:

Model:	BL+60-3-C1-115-F400	BL+60-3-C2-1-P
Power:	60 KVA unit, 3 phase output	60 KVA, 3 phase output
Input:	120/208 VAC, 57-63 Hz	220/380 VAC, 47-53 Hz
Output:	115/200 VAC with fixed frequency of 400 Hz	0-132 VAC
Options:		P: Programmable controller



T: +44 1268 568200
E: sales@powerstax.com
w: www.powerstax.com

Proudly made

in the U.S.A.

www.behlman.com

ORBIT POWER GROUP
Behlman Electronics

Headquarters:
80 Cabot Court, Hauppauge, NY 11788
631 435-0410 800 874-6727
Fax: 631 951-4341

2363 Teller Road, Suite 108
Newbury Park, CA 91320
805 375-7046 800 456-2006
Fax: 805 498-2147

sales@behlman.com